

**DESCRIPTION**

The **GEFCO Select #EE C133LED Freestanding Submersible LED Light Fixture** is a very low profile 4 color in 1 submersible light providing medium dispersion of light and color changing rendition for low to medium height spray effects or waterfalls. The light fixture is provided with integral rock guard for installation with either wall or floor mounted applications. The adjustability for light projection is at 45 degrees in any direction off of vertical. Clear lens is normally provided with the option of 4 ea. MR 16 5W colored (or white) LED lamps. The maximum wattage is 4x50 Watts at 12 Volts . Optional colors available are blue, red, green; yellow & dichroic. Special order colors are available in dichroic colors.

**TYPICAL SPECIFICATIONS:**

- \* **GEFCO Select #EE C133LV** LED Freestanding Submersible 12V Light Fixture:
  - 45° directional adjust ability.
  - cast bronze housing.
  - water cooled.
  - stainless steel fitted, neoprene o-ring seal.
  - option: rock guard integral with fixture (see lens options).
  - cast bronze and brass stand.
  - U.L. Listed to max..... 50W.
  - 4x 50 Watt, 12 V. max.....
  - 9 feet of 16/9 cable.
  - clear tempered cast boron silicate lens.
  - option: flat clear armored lens (in lieu of rock guard)
  - lamp required MR 16 specify colors (white,blue,red,green).
  - **LAMP NOT INCLUDED.**

**OPTIONS**

120V Version - This Fixture is available with GU-10 Sockets for 120VAC operation

LAMP - The lamp is not ordinarily supplied, but can be upon request at additional cost. Please state voltage and color. Available are 50W 12V white, blue, red, green, yellow and dichroic.

CORD LENGTH - Cable longer than 9'- 0" is optional and can be supplied at an extra cost. (Note: NEC 2008 does not permit more than 10 feet of cord to be exposed; the design of appropriate protection is required).


**REPLACEMENT PARTS:**

- A Lens.
- B Lens gasket.
- C Face ring
- D Stand.
- E Yoke.
- F Fixture mounting SST screw set.



**IMPORTANT INFORMATION**

The NEC Article 680-51(D) requires that "electric equipment which depends on submersion for safe operation shall be protected against overheating by a low water cutoff or by other approved means when not submerged." Other approved means are either GEFCO #EE115-Series or #EE140-Series water level control devices.



**TOP VIEW**

