



GEFCO SELECT EE154HV 120VAC DMX Controlled COLOR LED Lights

DESCRIPTION

The **GEFCO Select #EE154NHVC COLOR LED Submersible Niche Mounted Light Fixture** is constructed to provide relative narrow dispersion of light and provides an approx. 1.6 Million computer controlled color rendition for low to medium range height spray effects or waterfalls. The fixture can also be equipped with single colored (optional DMX controlled) lighting boards in solid white, green, red, blue and amber (see GEFCO Select #EE154C-ZZ). They can also be mounted in a slab hung or niche mounted application. The light has available projection beam angles of up to 35°. It is equipped with a clear tempered convex glass lens (flat lens optional). Variance in the height can be achieved by adjusting the stand to the elevation desired. Optionally this light can be controlled via DMX512 Protocol for dimming purposes (1 DMX channel) using DMX controllers such as GEFCO #EE960 DMX controller or other 3rd. party DMX controllers (NOT INCLUDED).

Limits for this fixture are 100 Watts MAX. at 120VAC. These fixtures must be connected to a common commercially available U.L. Listed Class A GFCI breakers. Connections are made to standard U.L. Listed underwater junction boxes such as GEFCO Select #EE106, #EE108 or #EE110 series using U.L. Listed cord seals such as GEFCO Select #EE112-01 Series Cord Seals.

Each COLOR LED light is optioally DMX addressable by serial number at the time of installation using a DMX lighting address unit (sold separately) mounted in the field or at the factory. Each light uses 1 DMX channel. This light can be controlled from a GEFCO Select #EE960 DMX Dual Universe Controller or other 3rd party DMX controllers (ORDER SEPARATELY) that will control up to 500 light fixtures per universe or any other third party DMX512 standard show controller. This light should be operated submerged up to 12" (30CM), wet location OK.

**USE ONLY IN WET OR SUBMERGED LOCATIONS
!!!DO NOT USE IN DRY CONDITION!!!**

For best light disbursement the flat lens configuration is recommended.

TYPICAL SPECIFICATIONS:

* GEFCO Select #EE154NHVC COLOR LED-ZZ Niche Mounted Submersible Light Fixture:

- cast bronze body & face ring, SST fitted.
- 6 LED Lighting Board with DMX ON BOARD.
- U.L. Listed: 100W, 120VAC.
- 9 feet of 16/3 (or 18/5 -DMX) single SOOW cable.
- ZZ = beam angle specify 20° or 35° (20° standard) ^
- clear tempered convex glass lens (flat lens optional).
- silicon lens gaskets.
- bronze, brass and SST fitted mounting niche.
- rated IP68 to 30CM, for use in wet conditions.
- **ROCK GUARD NOT INCLUDED** (order separately).
- **DMX CONTROLLER NOT INCLUDED.**

OPTIONAL ITEMS:




- ZZ = Beam angles. Available are 20° or 35° (specify).
- Tempered Flat Lens.
- GEFCO Select #EE154-10 Rock Guard.
- GEFCO Select #EE960 RGB/ RGBW/ RGBAW 512/1024-Channel DMX Controller.
- GEFCO Select #EE965 or #EE966 MUSIC Multimedia RGB/RGBW/ RGBAW 1024-Channel Show Controller.

OPTIONAL ITEMS:


- CORD LENGTH - Cable longer than 9'- 0" is optional and can be supplied at an extra cost. However, only 10'- 0" of **exposed** cable is permissible per NEC.

IMPORTANT

The designers, installers and end users utilizing the electrical equipment described herein assume full responsibility for the compliance with the N.E.C. and it's applicable articles, intents and consequences. Where the manufacturer and/or the supplier of the electrical equipment described herein does not control the application or usage, he assumes no responsibility whatsoever for any consequences arising out of the application, installation and/or usage of this or any other equipment and/or materials.



SCALE: NONE



IMPORTANT

*Dimensions and/or Materials
subject to change without notice*