

**DESCRIPTION**

The **GEFCO Select #PM402-Series Submersible Electric Pump** is designed for small to medium output requirements of up to 2500 GPH at 10 FH. This pump is also equipped with a low water shut-off device to prevent the pump from running in a dry condition. It features an epoxy coated housing for long equipment life and corrosion protection. In order to prevent debris from entering the system this model is equipped with a removable plastic screen for cleaning. This pump is suitable for simple one-jet water features or waterfalls.

**TYPICAL SPECIFICATIONS:**

- \* **GEFCO Select #PM402-8-CBA** Submersible Pump:
  - 3/8 HP motor, 115V, 1Phase, 60 HZ.
  - cast bronze housing w/ epoxy coating
  - lifetime supply of motor lubricant.
  - 6 feet of 18/3 underwater cable.
  - rated @ 2500 GPH at 10 FH, 14 amps.
  - U.L. Listed. - buna-n seal
  - 1 1/2" N.P.T. discharge connection.

**IMPORTANT REQUIREMENT**

The 2014 NEC Article 680-51(A) in part requires that submersible pumps shall be protected with CLASS "A" Ground Fault Circuit Interruptors (GFCI).

**IMPORTANT NOTE**

The designers, installers and end users utilizing the electrical equipment described herein assume full responsibility for the compliance with the NEC and it's applicable articles, intents and consequences. Where the manufacturer and/or the supplier of the electrical equipment described herein does not control the application or usage, he assumes no responsibility whatsoever for any consequences arising out of the application, installation and/or usage of this or any other equipment and/or materials.

**IMPORTANT**

Dimensions, Manufacturers and/or Materials subject to change without notice

