

**DESCRIPTION**

The **GEFCO Select #SE214-1 Fluid Switch Operated Stream Jet Assembly** is a fluid diverter unit that allows the rapid switching of fluid by non-mechanical means (no valve) in the main water stream. There is only one small solenoid valve that controls atmospheric pressure inside the switch path way. There are no shocks or water hammer in the water piping. Typical switching speed is an impressive fast 0.1 sec. the performance chart below is for a combination of the GEFCO Select #214-1 Fluid Switch when used with a GEFCO Select #SE105-06 stream jet with flow straightener (ordered separately).

The GEFCO select #SE214-1 Fluid Switch is typically connected directly to a GEFCO #PE109-10 slab penetration or with a high pressure hose to a GEFCO #PE109-10 slab penetration or common water manifold.

The GEFCO Select #SE214-1 Fluid Switch will operate in open air AS WELL AS TOTALLY SUBMERGED except for the Static Airline and the spray effect jet used.

The Control Solenoid Valve is made of ALL SST and can be ordered in operating Voltages of 24VDC (RECOMMENDED) or 12VAC (please specify).

The Main switch body is made of ultraviolet-safe injection molded ABS Plastic. and features a 1" NPT water connection, a 3/4" discharge and exhaust to the floor.

The GEFCO Select #SE214 Fluid Switch will operate other spray effects as well. Consult the Factory for performances using other jets.

**IMPORTANT NOTE:**

**THE LISTED PERFORMANCE IS ONLY VALID WHEN USING GEFCO SELECT #SE105-06 STREAM JETS!**

**TYPICAL SPECIFICATIONS:**

**\* GEFCO Select #SE214-1 Fluid Switch (Stream Jet):**

- 1" NPT Inlet.
- (2) 3/4" NPT Jet outlets.
- UV Hardened ABS Injection Molded Plastic.
- Submersible 24VDC or 12VAC (specify) SST Solenoid valve
- 9 feet of UL Listed Submersible Cable (ST18/3)
- GEFCO Select #SE105-06 Stream jet, Brass,
- GEFCO Custom 3/4" Flow straightener.

**ADDITIONAL INFORMATION:**

- \* Suction Straining required to be: 0.125" MAX.
- \* ALL PERFORMANCES ARE AT THE JET
- NOT AT THE PUMP !

**REPLACEMENT PARTS:**


- 1 Solenoid valve coil (specify voltage)
- 2 Solenoid valve diaphragm kit.
- 3 Solenoid valve mounting bolt set.
- 4 Solenoid valve mounting seal kit (O-rings).

**IMPORTANT REQUIREMENT**

Designers and Engineers shall be responsible for the accuracy of system flow rates and especially system head loss requirements. Stated flows and head pressure requirements for any listed spray height are required AT THE NOZZLE. Extrapolations for unlisted spray heights are at the sole responsibility of the Designers and/or Engineers.

**IMPORTANT**

Dimensions, Manufacturers and/or Materials subject to change without notice



#SE 214-1			NEEDED
T	1"NPT		SAFE
DO	0.500"		INFO
OH	15.25"		IN PSI:
SPRAY HEIGHT	GPM	FT. HEAD	EXIT PRESS.
03'	11	25	1.30
05'	14	45	2.30
08'	18	60	3.50
10'	20	74	4.50
15'	25	82	6.50